Assembly Guide





Step 1

1x Frame, Seat & Bag 4x Wheels 2x Brake Handles 2x Star Knobs & Bolts 4x Screw Knobs 1x Backrest After removing all the plastic wrapping open the Rollator by pushing down on the middle bar. Ensure the side arms are flat & in place.



Attach the 4 wheels using the push-buttons. Adjust the height and insert the screw knobs for each wheel. Tighten firmly.

Operating Guide

Hand Brake - Walking

Hand Brake - Sitting



200

Before sitting - push

clicks into place, this

will lock the wheels.

NOTE: Always lock

brakes before sitting.

brake lever down until it

Brake Adjustment



The brake tension can be tightened or loosened by adjusting the nut above the brake cable support.





Insert the brake

handles into the sides

of the frame. Place star

knob through the holes

at the desired handle

height and tighten.

Step 4



Place the padded backrest into the brackets on the frame at the rear of the seat. Press buttons and click into place

Finished Assembly



When assembled your rollator should look like this.



the brake.

While walking -

squeeze handle and

brake lever together

(upwards) to activate

Safety Warnings





Take care when folding

the rollator and keep

fingers, feet and legs

mechanism or frame.

clear of the folding

Care when walking



Take care when walking with the rollator, especially on a slope. Use the brakes to maintain a steady and controlled pace. Do not stand on seat



Do not stand or kneel on the rollator seat & do not push people around when seated on the rollator seat as an injury may occur.